

Positive Displacement Blowers

24 URAI

- Shaft Configurations available: Left, Right, Top, Bottom
- Detachable steel mounting feet
- Rigid one-piece cast iron casing
- Connections in standard pipe sizes
- Straight, precision machined two-lobe impellers
- Splash oil lubricated gear and drive ends
- Carburized and ground alloy steel spur timing gears
- Anti-Friction gears
- Ground steel shafts
- Center Timed for rotation in either direction



Specs

Flow Range	to 148 CFM
Max Δ Pressure	7 PSI
Max Δ Vacuum	15" Hg
Maximum RPM	5275
Minimum RPM	1530
Max Δ T	210°F
Connection Size	2" FPT
Shaft Dia.	0.625"
Min Sheave Dia.	4"
Drive End Lubrication	Grease
Gear End Lubrication	Oil
Oil Sump Gear End Horiz Config	6.1 oz.
Oil Sump Gear End Vert Config	3.4 oz.
Bare Unit Weight	46 lbs.
Shipping Weight	50 lbs.
Shipping Container	Box
Box Size (L x W x H)	17" x 16" x 12"

Roots[®] Blowers



Direct Drop-in Replacement for:

Sutorbilt Model 2LP

Tuthill Model 2004

Blower Packages

Blower Repair

Blower Oil and Parts

Sound Enclosures

Filters & Silencers

Filter Elements

Convey Line Components

Global Technology & Engineering



26426 H HWY
EXCELSIOR SPRINGS, MO 64024
SALES@GLOBALTECHENG.COM
816-630-3500