

Positive Displacement Blowers

615 URAI

- Shaft Configurations available: Left, Right, Top, Bottom
- Detachable steel mounting feet
- Rigid one-piece cast iron casing
- Connections in standard pipe sizes
- Straight, precision machined two-lobe impellers
- Splash oil lubricated gear and drive ends
- Carburized and ground alloy steel spur timing gears
- Anti-Friction gears
- Ground steel shafts
- Center Timed for rotation in either direction



Specs

Flow Range	to 1583 CFM
Max Δ Pressure	7 PSI
Max Δ Vacuum	12" Hg
Maximum RPM	2350
Minimum RPM	636
Max Δ T	130°F
Connection Size	6" Flange
Shaft Dia.	1.375"
Min Sheave Dia.	8"
Drive End Lubrication	Grease
Gear End Lubrication	Oil
Oil Sump Gear End Horiz Config	52 oz.
Oil Sump Gear End Vert Config	28.3 oz.
Bare Unit Weight	425 lbs.
Shipping Weight	~475 lbs.
Shipping Container	Wood Skid
Box Size (L x W x H)	54" x 32" x 25"

Roots[®] Blowers



Direct Drop-in Replacement for:

Sutorbilt Model 6LP

Tuthill Model 6015

Blower Packages

Blower Repair

Blower Oil and Parts

Sound Enclosures

Filters & Silencers

Filter Elements

Convey Line Components



26426 H HWY
EXCELSIOR SPRINGS, MO 64024
SALES@GLOBALTECHENG.COM
816-630-3500