

# Positive Displacement Blowers

## 65 URAI

- Shaft Configurations available: Left, Right, Top, Bottom
- Detachable steel mounting feet
- Rigid one-piece cast iron casing
- Connections in standard pipe sizes
- Straight, precision machined two-lobe impellers
- Splash oil lubricated gear and drive ends
- Carburized and ground alloy steel spur timing gears
- Anti-Friction gears
- Ground steel shafts
- Center Timed for rotation in either direction



### Specs

Flow Range	to 526 CFM
Max ΔPressure	15 PSI
Max ΔVacuum	16" Hg
Maximum RPM	2350
Minimum RPM	636
Max ΔT	250°F
Connection Size	3" FPT
Shaft Dia.	1.375"
Min Sheave Dia.	8"
Drive End Lubrication	Grease
Gear End Lubrication	Oil
Oil Sump Gear End Horiz Config	52 oz.
Oil Sump Gear End Vert Config	28.3 oz.
Bare Unit Weight	245 lbs.
Shipping Weight	~305 lbs.
Shipping Container	Wood Skid
Box Size (L x W x H)	32" x 29" x 31"

## Roots<sup>®</sup> Blowers



**Direct Drop-in Replacement for:**

**Sutorbilt Model 6HP**

**Tuthill Model 6005**

**Blower Packages**

**Blower Repair**

**Blower Oil and Parts**

**Sound Enclosures**

**Filters & Silencers**

**Filter Elements**

**Convey Line Components**

**Global Technology & Engineering**

26426 H HWY  
EXCELSIOR SPRINGS, MO 64024  
SALES@GLOBALTECHENG.COM  
816-630-3500