

Positive Displacement Blowers

76 URAI

- Shaft Configurations available: Left, Right, Top, Bottom
- Detachable steel mounting feet
- Rigid one-piece cast iron casing
- Connections in standard pipe sizes
- Straight, precision machined two-lobe impellers
- Splash oil lubricated gear and drive ends
- Carburized and ground alloy steel spur timing gears
- Anti-Friction gears
- Ground steel shafts
- Center Timed for rotation in either direction



Specs

Flow Range	to 765 CFM
Max ΔPressure	15 PSI
Max ΔVacuum	16" Hg
Maximum RPM	2050
Minimum RPM	545
Max ΔT	250°F
Connection Size	4" FPT
Shaft Dia.	1.562"
Min Sheave Dia.	9.5"
Drive End Lubrication	Grease
Gear End Lubrication	Oil
Oil Sump Gear End Horiz Config	59.5 oz.
Oil Sump Gear End Vert Config	32.3 oz.
Bare Unit Weight	400 lbs.
Shipping Weight	~450 lbs.
Shipping Container	Wood Skid
Box Size (L x W x H)	32" x 29" x 35"

Roots[®] Blowers



Direct Drop-in Replacement for:

Sutorbilt Model 7HP

Tuthill Model 7006

Blower Packages

Blower Repair

Blower Oil and Parts

Sound Enclosures

Filters & Silencers

Filter Elements

Convey Line Components

Global Technology & Engineering

26426 H HWY
EXCELSIOR SPRINGS, MO 64024
SALES@GLOBALTECHENG.COM
816-630-3500